

# SPRING HANGERS

## Variable Spring

## Check List for Requesting a Quote or Ordering

Page \_\_\_ of \_\_\_



Anvil International  
Precision Park  
160 Frenchtown Rd.  
North Kingstown, RI 02852

For technical information regarding  
Variable Springs Call or Email:  
Phone Number: (401) 886-3020  
Email: [eps\\_contact@anvilintl.com](mailto:eps_contact@anvilintl.com)

**Finish:** Standard Primer: \_\_\_\_\_ Galvanized: \_\_\_\_\_ Special Coating: \_\_\_\_\_

**Quantity:** \_\_\_\_\_

**Figure No.:** Options are:  82,  B-268,  98,  Triple,  Quadruple  
or:  C-82,  C-268,  C-98,  Triple-CR,  Quadruple-CR

**Size:** Options are: #0 through #22 (B-268 / C-268 also available in #00 and #000) \_\_\_\_\_

**Type:** Options are: A through G\* \_\_\_\_\_

**Hot (Operating or Design) Load (lbs):** \_\_\_\_\_ (optional)\*\*

**Cold/Installed (Factory Set) Load (lbs):** \_\_\_\_\_ (optional)\*\*

**Vertical Movement:** \_\_\_\_\_ + (up) or - (down) (optional)\*\*

**Mark Number:** \_\_\_\_\_ (If Required)

**Travel Stops:** Yes: \_\_\_\_\_ No: \_\_\_\_\_

*If travel stops are ordered and hot & cold loads are not provided, then the spring will be set to mid range load.*

**Lifting Lugs:** Yes: \_\_\_\_\_ No: \_\_\_\_\_

*Available on sizes weighing 100 lbs or more.*

### Notes:

\* Type G Springs must also include the C-to-C dimension & the load per spring.

\*\* Anvil will determine the appropriate Figure Number and will calculate the Cold Load when only the Hot Load and movement are specified.